



| 直管蛍光灯 T4管 FLR | | 品種 | 型番(コード) | 品名 | 定格電力 (W) | 色温度 | ランプ径 (mm) | 長さ (mm) | 口金 | 全光束 (lm) | 定格寿命 (h) | 価格 (¥) |
|-----------------------------------------------------------------------------------|-----------|-------|-----------|----|----------|-------|-----------|---------|----|----------|----------|---------|
|  | 20W (電球色) | R5340 | FLR20WT4L | | 17 | 2700K | 12 | 510 | G5 | 900 | 8,000 | (2,800) |
| | 20W (白 色) | R5341 | FLR20WT4W | | 17 | 4100K | 12 | 510 | G5 | 985 | 8,000 | (2,800) |
| | 20W (昼光色) | R5342 | FLR20WT4D | | 17 | 6400K | 12 | 510 | G5 | 985 | 8,000 | (2,800) |
| | 23W (電球色) | R5343 | FLR23WT4L | | 21 | 2700K | 12 | 790 | G5 | 1,150 | 8,000 | (3,300) |
| | 23W (白 色) | R5344 | FLR23WT4W | | 21 | 4100K | 12 | 790 | G5 | 1,260 | 8,000 | (3,300) |
| | 23W (昼光色) | R5345 | FLR23WT4D | | 21 | 6400K | 12 | 790 | G5 | 1,260 | 8,000 | (3,300) |
| | 27W (電球色) | R5346 | FLR27WT4L | | 26 | 2700K | 12 | 1,090 | G5 | 1,350 | 8,000 | (3,800) |
| | 27W (白 色) | R5347 | FLR27WT4W | | 26 | 4100K | 12 | 1,090 | G5 | 1,480 | 8,000 | (3,800) |
| | 27W (昼光色) | R5348 | FLR27WT4D | | 26 | 6400K | 12 | 1,090 | G5 | 1,480 | 8,000 | (3,800) |

| 直管蛍光灯 T5管 FHF | | 品種 | 型番(コード) | 品名 | 定格電力 (W) | 色温度 | ランプ径 (mm) | 長さ (mm) | 口金 | 全光束 (lm) | 定格寿命 (h) | 価格 (¥) |
|-----------------------------------------------------------------------------------|-----------|--------|-------------|----|----------|-------|-----------|---------|----|---------------|----------|---------|
|  | 24W (電球色) | R5072 | FHF24SEL | | 22.5 | 3000K | 16 | 549 | G5 | 1,770 (1,950) | 9,000 | (1,100) |
| | 24W (白 色) | R5073 | FHF24SEW | | 22.5 | 4000K | 16 | 549 | G5 | 1,770 (1,950) | 9,000 | (1,100) |
| | 24W (昼白色) | R5074 | FHF24SEN | | 22.5 | 5000K | 16 | 549 | G5 | 1,770 (1,950) | 9,000 | (1,100) |
| | 54W (電球色) | A-59L | F54W/T5/830 | | 54 | 3000K | 16 | 1,149 | G5 | 4,460 (5,000) | 12,000 | 1,700 |
| | 54W (温白色) | A-59WW | F54W/T5/835 | | 54 | 3500K | 16 | 1,149 | G5 | 4,460 (5,000) | 12,000 | 1,700 |
| | 54W (白 色) | A-59W | F54W/T5/840 | | 54 | 4000K | 16 | 1,149 | G5 | 4,460 (5,000) | 12,000 | 1,700 |
| | 54W (昼白色) | A-59NM | FHF54SEN-ED | | 54 | 5000K | 16 | 1,149 | G5 | 4,550 (5,000) | 12,000 | 1,700 |
| | 54W (電球色) | R5075 | FHF54SEL | | 54 | 3000K | 16 | 1,149 | G5 | 4,550 (5,000) | 12,000 | (1,700) |
| | 54W (昼白色) | R5077 | FHF54SEN | | 54 | 5000K | 16 | 1,149 | G5 | 4,550 (5,000) | 12,000 | (1,700) |

全光束の () 内の値は、周囲温度35℃のもの です。

| シームレス蛍光灯 T5管 FHE | | 品種 | 型番(コード) | 品名 | 定格電力 (W) | 色温度 | ランプ径 (mm) | 長さ (mm) | 口金 | 全光束 (lm) | 定格寿命 (h) | 価格 (¥) |
|-------------------------------------------------------------------------------------|--------------|---------|---------------|----|----------|-------|-----------|---------|----|-------------|----------|--------|
|  | L= 500 (電球色) | A-81LA | FHE500T5-EL | | 16/10 | 2800K | 16 | 497 | — | 1,380/ 900 | 10,000 | 4,800 |
| | L= 500 (温白色) | A-81WWA | FHE500T5-EWW | | 16/10 | 3500K | 16 | 497 | — | 1,380/ 900 | 10,000 | 4,800 |
| | L= 500 (白 色) | A-81WA | FHE500T5-EW | | 16/10 | 4200K | 16 | 497 | — | 1,380/ 900 | 10,000 | 4,800 |
| | L= 500 (昼白色) | A-81NA | FHE500T5-EN | | 16/10 | 5000K | 16 | 497 | — | 1,340/ 880 | 10,000 | 4,800 |
| | L= 550 (電球色) | A-82LA | FHE550T5-EL | | 17 | 2800K | 16 | 547 | — | 1,530 | 10,000 | 4,800 |
| | L= 550 (温白色) | A-82WWA | FHE550T5-EWW | | 17 | 3500K | 16 | 547 | — | 1,530 | 10,000 | 4,800 |
| | L= 550 (白 色) | A-82WA | FHE550T5-EW | | 17 | 4200K | 16 | 547 | — | 1,530 | 10,000 | 4,800 |
| | L= 550 (昼白色) | A-82NA | FHE550T5-EN | | 17 | 5000K | 16 | 547 | — | 1,490 | 10,000 | 4,800 |
| | L= 850 (電球色) | A-65LA | FHE850T5-EL | | 26/15 | 2800K | 16 | 847 | — | 2,430/1,520 | 12,000 | 4,800 |
| | L= 850 (温白色) | A-65WWA | FHE850T5-EWW | | 26/15 | 3500K | 16 | 847 | — | 2,430/1,520 | 12,000 | 4,800 |
| | L= 850 (白 色) | A-65WA | FHE850T5-EW | | 26/15 | 4200K | 16 | 847 | — | 2,430/1,520 | 12,000 | 4,800 |
| | L= 850 (昼白色) | A-65NA | FHE850T5-EN | | 26/15 | 5000K | 16 | 847 | — | 2,370/1,480 | 12,000 | 4,800 |
| | L=1000 (電球色) | A-66LA | FHE1000T5-EL | | 30/18 | 2800K | 16 | 997 | — | 2,890/1,810 | 12,000 | 4,800 |
| | L=1000 (温白色) | A-66WWA | FHE1000T5-EWW | | 30/18 | 3500K | 16 | 997 | — | 2,890/1,810 | 12,000 | 4,800 |
| | L=1000 (白 色) | A-66WA | FHE1000T5-EW | | 30/18 | 4200K | 16 | 997 | — | 2,890/1,810 | 12,000 | 4,800 |
| | L=1000 (昼白色) | A-66NA | FHE1000T5-EN | | 30/18 | 5000K | 16 | 997 | — | 2,810/1,760 | 12,000 | 4,800 |
| | L=1250 (電球色) | A-67LA | FHE1250T5-EL | | 37/22 | 2800K | 16 | 1,247 | — | 3,650/2,280 | 12,000 | 5,500 |
| | L=1250 (温白色) | A-67WWA | FHE1250T5-EWW | | 37/22 | 3500K | 16 | 1,247 | — | 3,650/2,280 | 12,000 | 5,500 |
| | L=1250 (白 色) | A-67WA | FHE1250T5-EW | | 37/22 | 4200K | 16 | 1,247 | — | 3,650/2,280 | 12,000 | 5,500 |
| | L=1250 (昼白色) | A-67NA | FHE1250T5-EN | | 37/22 | 5000K | 16 | 1,247 | — | 3,550/2,220 | 12,000 | 5,500 |
| | L=1500 (電球色) | A-68LA | FHE1500T5-EL | | 44/27 | 2800K | 16 | 1,497 | — | 4,400/2,750 | 12,000 | 5,500 |
| | L=1500 (温白色) | A-68WWA | FHE1500T5-EWW | | 44/27 | 3500K | 16 | 1,497 | — | 4,400/2,750 | 12,000 | 5,500 |
| | L=1500 (白 色) | A-68WA | FHE1500T5-EW | | 44/27 | 4200K | 16 | 1,497 | — | 4,400/2,750 | 12,000 | 5,500 |
| | L=1500 (昼白色) | A-68NA | FHE1500T5-EN | | 44/27 | 5000K | 16 | 1,497 | — | 4,280/2,680 | 12,000 | 5,500 |

※定格電力、全光束欄の左は高照度タイプ時、右は高効率タイプ時の値です。