


3000TYPE



■本体



100V	電源 内蔵	無線 調光	120°	360°
調色				
光束維持時間 40,000h (光束維持率85%)				

本体価格

¥49,500

消費電力

【S】48.1W [100V]
<無線調光タイプ>
無線モジュール付
調光率：1~100%


LEDモジュール【S】

本体：アルミダイキャスト（白艶消／黒艶消）
重：1.6kg
電源内蔵
LED交換不可

2400TYPE



■本体



100V	電源 内蔵	無線 調光	120°	360°
調色				
光束維持時間 40,000h (光束維持率85%)				

本体価格

¥44,800

消費電力

【S】39.2W [100V]
<無線調光タイプ>
無線モジュール付
調光率：1~100%

LEDモジュール【S】

本体：アルミダイキャスト（白艶消／黒艶消）
重：1.6kg
電源内蔵
LED交換不可

20000K-1800K相当




17°

ビーム角

18°

ナロー・モデル
配光



SXS3046W (白)	定格光束: 3511lm						
SXS3046B (黒)	【S】48.1W 72.9lm/W (4000K 白色時)						
1/2 照度 1/2C-1m高	4000K時	精肉	鮮魚	青果	惣菜	lx	m
17°	26700	300	21900	25600	25600	26700	1
18°	6670	600	5470	6400	6400	6670	2
50000	2960	900	2430	2850	2850	2960	3
10000	1670	1200	1370	1600	1600	1670	4
5000							
2000							
1000							
500							
200							
100							
50							
20							
10							
5							
2							
1							
0							
1							
2							
3							
3m	2	1	0	1	2	3	
TAA4522598A11G							

20000K-1800K相当




17°

ビーム角

17°

ナロー・モデル
配光



SXS3049W (白)	定格光束: 3018lm						
SXS3049B (黒)	【S】39.2W 76.9lm/W (4000K 白色時)						
1/2 照度 1/2C-1m高	4000K時	精肉	鮮魚	青果	惣菜	lx	m
17°	24600	300	20200	23700	23700	24600	1
18°	6140	600	5050	5910	5910	6140	2
50000	2740	900	2240	2630	2630	2740	3
10000	1540	1200	1260	1480	1480	1540	4
5000							
2000							
1000							
500							
200							
100							
50							
20							
10							
5							
2							
1							
0							
1							
2							
3							
3m	2	1	0	1	2	3	
TAA7522601A11G							




22°

ビーム角

23°

中角配光



SXS3047W (白)	定格光束: 3629lm						
SXS3047B (黒)	【S】48.1W 75.4lm/W (4000K 白色時)						
1/2 照度 1/2C-1m高	4000K時	精肉	鮮魚	青果	惣菜	lx	m
22°	18600	390	15300	17900	17900	18600	1
23°	4650	780	3810	4460	4460	4650	2
20000	2070	1170	1690	1980	1980	2070	3
10000	1160	1560	950	1120	1120	1160	4
5000							
2000							
1000							
500							
200							
100							
50							
20							
10							
5							
2							
1							
0							
1							
2							
3							
3m	2	1	0	1	2	3	
TAA5322599A11G							




22°

ビーム角

23°

中角配光



SXS3050W (白)	定格光束: 3130lm						
SXS3050B (黒)	【S】39.2W 79.8lm/W (4000K 白色時)						
1/2 照度 1/2C-1m高	4000K時	精肉	鮮魚	青果	惣菜	lx	m
22°	16300	390	13400	15700	15700	16300	1
23°	4080	780	3350	3920	3920	4080	2
20000	1820	1170	1490	1740	1740	1820	3
10000	1020	1560	840	980	980	1020	4
5000							
2000							
1000							
500							
200							
100							
50							
20							
10							
5							
2							
1				</			